



**gateway for BL20 I/O system
interface for DeviceNet incl. supply
BL20-GWBR-DNET**



- rotary coding switch for adjustment of the node address
- degree of protection IP20
- 2 x end brackets BL20-WEW35/2-SW
- 1 x end plate BL20-ABPL
- with integrated supply
- LEDs for display of supply voltage, common alarm and bus errors
- interface between the BL20 system and DeviceNet
- 125 / 250 / 500 kbps
- the connection to DeviceNet is established via an Open-Style-Connector

Type	BL20-GWBR-DNET
Ident-No.	6827168
Supply voltage	24VDC
System power supply	24 VDC / 5 VDC
Field supply	24 VDC
Admissible range	18...30 VDC
Rated current from module bus	≤ 250 mA
Max. field supply current	10 A
Max. system supply current	1.2 A
Voltage supply connection	screw connection
Fieldbus transmission rate	125 / 250 / 500 kbps
Fieldbus addressing	2 rotary switches
Fieldbus addressing range	0...63
Service interface	PS/2 socket for I/O-ASSISTANT
Fieldbus connection technology	open connector
Fieldbus termination	external
Dimensions (W x L x H)	50.6x114.8x74.4mm
Approvals	CE, cULus, zone2, ClassI,div.2.
Operating temperature	0...55 °C
Storage temperature	-25 to +85 °C
Relative humidity	5 to 95% (internal), Level RH-2, no condensation (at 45 °C storage)
Vibration test	acc. to EN 61131
Shock test	acc. to IEC 68-2-27
Drop and topple	acc. to IEC 68-2-31 and free fall to IEC 68-2-32
Electro-magnetic compatibility	acc. to EN 50,082-2
Protection class	IP20
Included in scope of supply	2 x end brackets BL20-WEW-35/2-SW, 1 x end plate BL20-ABPL

Field supply/system supply




Functional principle

BL20 gateways are the head component of a BL20 station. They are designed to interface the modular fieldbus nodes to the higher level fieldbus (PROFIBUS-DP, DeviceNet, CANopen, Ethernet).

All BL20 electronic modules communicate over the internal module bus, the data of which is transferred to the fieldbus via the gateway, so that all I/O modules can be configured independently of the bus system.

gateway for BL20 I/O system
 interface for DeviceNet incl. supply
 BL20-GWBR-DNET

Wiring accessories

Type code	Ident-No.	Short text	Dimension drawing
I/O-ASSISTANT-KA-BEL-BL20/BL67	6827133	RS232 adapter cable for the BL67/BL20 service interface	
BS3511/KLBUE4-31.5	6827342	Shield terminal and strain relief for bus cable	